



LABINCO L32 Basic Hotplate Magnetic Stirrer 20 ltr. 325°C

Description

Model L-32

- Speed 50-1250
- Cap. 10 liters
- Topplate Aluminum 195 mm. diam.
- Thermostatic controlled 50-320C
- Housing: 2 piece casted aluminum
- Electrostatically applied powder coated
- M-10 threaded support rod connection
- Supplied with te on magnetic stirring bar line cord and manual
- Hotplate 195 mm diam. Aluminium 50-1250 rpm
- Hotplate temperature 50-325C
- Stirring capacity 20 Ltr
- Dimensions (WxDxH) 200 x 250 x 135 mm
- Weight 4.2 kg
- Art.nr.32000 (230V) 32010 (115V)
- incl. spinbar

Additional Information

Number of positions	1
Max Quantity	20 ltr
Motor Rating input(W)	35W

Motor Rating output(W)	15 W
Speed display	analog
Speed range(rpm)	50 - 1250 rpm
Stirring bar length max(mm)	80 mm
Heat output	600 W
Heating rate	7 K/min
Heating temperature range	room temp. - 325 C
Heat control	analog
Heat control accuracy	1 K
Speed control	analog
Temperature constancy in medium	1 K
Dimensions (W x D x H)	200 x 250 x 135 mm
Weight(kg)	4.2 kg
Permissible ambient temperature	5 - 40 C
Permissible relative humidity	80 %
Protection class according to DIN EN 60529	IP 42
Voltage	220 - 230 V (115 / 100 V)
Frequency	50/60 Hz
Power input	635 W