



## LABINCO L80 PTFE Coated Hotplate 10 ltr. 325Â°C

### Description

#### Model L-80 St.steel

- Hotplate: Aluminium PTFE coating 145 mm diam.
- With Stainless Steel efficient reflectors
- Thermostatic controlled 50-320C
- Housing from casted aluminum
- Electrostatically applied powder coated
- M-10 threaded support rod connection
  
- Hotplate 145 mm diam. Aluminium PTFE Coated
- Hotplate temperature 50-325C
- Dimensions (WxDxH) 172 x 286 x 125 mm
- Weight 2 kg
- Art.nr.80002 (230V) 80012 (115V)

### Additional Information

<b>Number of positions</b>	1
<b>Max Quantity</b>	10 ltr
<b>Motor Rating input(W)</b>	'-
<b>Motor Rating output(W)</b>	'-
<b>Speed display</b>	'-
<b>Speed range(rpm)</b>	'-
<b>Stirring bar length max(mm)</b>	'-

---

<b>Heat output</b>	600 W
<b>Heating rate</b>	7 K/min
<b>Heating temperature range</b>	room temp. - 325 C
<b>Heat control</b>	analog
<b>Heat control accuracy</b>	1 K
<b>Speed control</b>	'-
<b>Adjustable safety circuit min</b>	'-
<b>Adjustable safety circuit max</b>	'-
<b>Connection for ext. temperature sensor</b>	'-
<b>Control accuracy with sensor</b>	'-
<b>Temperature constancy in medium</b>	1 K
<b>Dimensions (W x D x H)</b>	172 x 286 x 125 mm
<b>Weight(kg)</b>	2 kg
<b>Permissible ambient temperature</b>	5 - 40 C
<b>Permissible relative humidity</b>	80 %
<b>Protection class according to DIN EN 60529</b>	IP 42
<b>RS232 interface</b>	'-
<b>Analog output</b>	'-
<b>Voltage</b>	220 - 230 V (115 / 100 V)
<b>Frequency</b>	50/60 Hz
<b>Power input</b>	600 W