LABORTECHNIK FRÃ¶BEL GMBH
Bazienstr. 18f, D-88131 Lindau (0049)017676986491 | kontakt(at)labequip.de



LABINCO L80 St.St. Hotplate 10 ltr. 325Â°C

Description

Model L-80 St.steel

- Hotplate: St.steel 145 mm diam.
- With Stainless Steel effcient reflectors
- Thermostatic controlled 50-320C
- Housing from casted aluminum
- Electrostaticaly applied powder coated
- M-10 threaded support rod connection

- Hotplate 130 mm diam. Stainless steel
- Hotplate temperature 50-325C
- Dimensions (WxDxH) 172 x 286 x 125 mm
- Weight 2 kg
- Art.nr.80001 (230V) 80011 (115V)

Additional Information

Number of positions	1
Max Quantity	10 ltr
Motor Rating input(W)	'-
Motor Rating output(W)	'-
Speed display	'-
Speed range(rpm)	'-
Stirring bar length max(mm)	'-

LABORTECHNIK FRÃ¶BEL GMBH
Bazienstr. 18f, D-88131 Lindau (0049)017676986491 | kontakt(at)labequip.de

Heat output	600 W
Heating rate	7 K/min
Heating temperature range	room temp. - 325 C
Heat control	analog
Heat control accuracy	1 K
Speed control	'-
Adjustable safety circuit min	'-
Adjustable safety circuit max	'-
Connection for ext. temperature sensor	'-
Control accuracy with sensor	'-
Temperatureconstancyinmedium	1 K
Dimensions (W x D x H)	172 x 286 x 125 mm
Weight(kg)	2 kg
Permissible ambient temperature	5 - 40 C
Permissible relative humidity	80 %
Protection class according to DIN EN 60529	IP 42
RS232 interface	'-
Analog output	'-
Voltage	220 - 230 V (115 / 100 V)
Frequency	50/60 Hz
Power input	600 W