LABORTECHNIK FRÃ¶BEL GMBH
Bazienstr. 18f, D-88131 Lindau (0049)017676986491 | kontakt(at)labequip.de



LABINCO L81 Basic PTFE Coated Hotplate Magnetic Stirrer 10 ltr.

Description

Model Economy Hotplate Stirrers L-81

- Hotplate: Alumimum whit PTFE Caoting 145 mm diam.
- Capacity: 10 ltr
- rpm: 50 â?? 1250
- Stirring motors: are of the AC-motors type
- With Stainless Steel efficient reflectors
- Housing: casted aluminum
- Electrostaticaly applied powder coated
- M-10 threaded support rod connection
- Supplied with a teflon magnetic stirring bar line cord and manual

- Hotplate 145 mm diam. Aluminium PTFE coated 50 â?? 1250 rpm
- Hotplate temperature 50-325C
- Stirring capacity 10 Ltr
- Dimensions (WxDxH) 172 x 286 x 125 mm
- Weight 2.8 kg
- Art.nr.81002 (230V) 81012 (115V)
- Incl. spinbar

Additional Information

Number of positions	1
Max Quantity	10 ltr
Motor Rating input(W)	35 W

LABORTECHNIK FRÃ¶BEL GMBH
Bazienstr. 18f, D-88131 Lindau (0049)017676986491 | kontakt(at)labequip.de

Motor Rating output(W)	15 W
Speed display	analog
Speed range(rpm)	50 - 1250 rpm
Stirring bar length max(mm)	80 mm
Heat output	600 W
Heating rate	7 K/min
Heating temperature range	room temp. - 325 C
Heat control	analog
Heat control accuracy	1 K
Speed control	stepless
Temperatureconstancyinmedium	1 K
Dimensions (W x D x H)	172 x 286 x 125 mm
Weight(kg)	2.8 kg
Permissible ambient temperature	5 - 40 C
Permissible relative humidity	80 %
Protection class according to DIN EN 60529	IP 42
Voltage	220 - 230 V (115 / 100 V)
Frequency	50/60 Hz
Power input	635 W