**LABORTECHNIK FRÃ¶BEL GMBH**
Bazienstr. 18f, D-88131 Lindau (0049)017676986491 | kontakt(at)labequip.de



# LABINCO LD814 4-position Hotplate Magnetic Stirrer 4Ã?5 ltr. 350Â°C

## Description

- Topplate 4 x 120 mm diam. Aluminium 50-1250 rpm
- Hotplate temperature 25-350C (digital)
- 4 positions in one row
- Stirring capacity 4 x 5 Ltr
- Dimensions (WxDxH) 550 x 245 x 140 mm
- Weight 10 kg
- Temperature sensor on request
- Art.nr.81400 (230V)
- Incl. 4 x spinbar

- Topplate 4 x 120 mm diam. Aluminium 50-1250 rpm
- Hotplate temperature 25-350C (digital)
- 4 positions in one row
- Stirring capacity 4 x 5 Ltr
- Dimensions (WxDxH) 550 x 245 x 140 mm
- Weight 10 kg
- Temperature sensor on request
- Art.nr.81400 (230V)
- Incl. 4 x spinbar

## Additional Information

| | |
|---|---|
| **Number of positions** | 4 in one row |
| **Max Quantity** | 4 x 5 ltr |
| **Motor Rating input(W)** | 4 x 35W |

**LABORTECHNIK FRÃ¶BEL GMBH**
Bazienstr. 18f, D-88131 Lindau (0049)017676986491 | kontakt(at)labequip.de

| | |
|---|---|
| **Motor Rating output(W)** | 4 x 15 W |
| **Speed display** | analog |
| **Speed range(rpm)** | 50 - 1250rpm |
| **Stirring bar length max(mm)** | 60 mm |
| **Heat output** | 4 x 300 W |
| **Heating rate** | 7 K/min |
| **Heating temperature range** | room temp.- 350C |
| **Heat control** | digital |
| **Heat control accuracy** | 1 K |
| **Speed control** | stepless |
| **Connection for ext. temperature sensor** | on request |
| **Control accuracy with sensor** | 1 K |
| **Temperatureconstancyinmedium** | 1 K |
| **Dimensions (W x D x H)** | 550 x 245 x 140 mm |
| **Weight(kg)** | 10 kg |
| **Permissible ambient temperature** | 5 - 40 C |
| **Permissible relative humidity** | 80 % |
| **Protection class according to DIN EN 60529** | IP 42 |
| **Voltage** | 220 - 230 V |
| **Frequency** | 50/60 Hz |
| **Power input** | 1350 W |