LABORTECHNIK FRÃ¶BEL GMBH
Bazienstr. 18f, D-88131 Lindau (0049)017676986491 | kontakt(at)labequip.de



LABINCO LD816 6 position Hotplate Magnetic Stirrer 6Ã?5 ltr. 350Â°C

Description

- Topplate 6 x 120 mm diam. Aluminium 50-1250 rpm
- Hotplate temperature 25-350C (digital)
- 6 positions in one row
- Stirring capacity 6 x 5 Ltr
- Dimensions (WxDxH) 835 x 245 x 140 mm
- Weight 14 kg
- Temperature sensor on request
- Art.nr.81600 (230V)
- Incl. 6 x spinbar

- Topplate 6 x 120 mm diam. Aluminium 50-1250 rpm
- Hotplate temperature 25-350C (digital)
- 6 positions in one row
- Stirring capacity 6 x 5 Ltr
- Dimensions (WxDxH) 835 x 245 x 140 mm
- Weight 14 kg
- Temperature sensor on request
- Art.nr.81600 (230V)
- Incl. 6 x spinbar

Additional Information

Number of positions	6 in one row
Max Quantity	6 x 5 ltr
Motor Rating input(W)	6 x 35W

LABORTECHNIK FRÃ¶BEL GMBH
Bazienstr. 18f, D-88131 Lindau (0049)017676986491 | kontakt(at)labequip.de

Motor Rating output(W)	6 x 15 W
Speed display	analog
Speed range(rpm)	50 - 1250rpm
Stirring bar length max(mm)	60 mm
Heat output	6 x 300 W
Heating rate	7 K/min
Heating temperature range	room temp.- 350C
Heat control	digital
Heat control accuracy	1 K
Speed control	stepless
Connection for ext. temperature sensor	on request
Control accuracy with sensor	1 K
Temperatureconstancyinmedium	1 K
Dimensions (W x D x H)	835 x 245 x 140 mm
Weight(kg)	14 kg
Permissible ambient temperature	5 - 40 C
Permissible relative humidity	80 %
Protection class according to DIN EN 60529	IP 42
Voltage	220 - 230 V
Frequency	50/60 Hz
Power input	2050 W