



LABINCO LD844 4 position St.st. Hotplate Magnetic Stirrer

Description

- Topplate 4 x 120 mm diam. Stainless steel 50-1250 rpm
- Hotplate temperature 25-350C (digital)
- 4 positions in two rows of two.
- Stirring capacity 4 x 5 Ltr
- Dimensions (WxDxH) 345 x 385 x 185 mm
- Weight 10 kg
- Temperature sensor on request
- Art.nr.84401 (230V)
- Incl. 4 x spinbar

Additional Information

Number of positions	4 positions in two rows of two.
Max Quantity	4 x 5 ltr
Motor Rating input(W)	4 x 35W
Motor Rating output(W)	4 x 15 W
Speed display	analog
Speed range(rpm)	50 - 1250rpm
Stirring bar length max(mm)	60 mm
Heat output	4 x 300 W
Heating rate	7 K/min
Heating temperature range	room temp.- 350C
Heat control	digital

Heat control accuracy	1 K
Speed control	stepless
Adjustable safety circuit min	'-
Adjustable safety circuit max	'-
Connection for ext. temperature sensor	on request
Control accuracy with sensor	1 K
Temperature constancy in medium	1 K
Dimensions (W x D x H)	345 x 385 x 185 mm
Weight(kg)	10 kg
Permissible ambient temperature	5 - 40 C
Permissible relative humidity	80 %
Protection class according to DIN EN 60529	IP 42
RS232 interface	'-
Analog output	'-
Voltage	220 - 230 V
Frequency	50/60 Hz
Power input	1350 W