LABORTECHNIK FRÃ¶BEL GMBH
Bazienstr. 18f, D-88131 Lindau (0049)017676986491 | kontakt(at)labequip.de



LABINCO LD814 4 position PTFE Coated Hotplate Magnetic Stirrer

Beschreibung

- Topplate 4 x 120 mm diam. Aluminium PTFE Coated 50-1250 rpm
- Hotplate temperature 25-350C (digital)
- 4 positions in one row
- Stirring capacity 4 x 5 Ltr
- Dimensions (WxDxH) 550 x 245 x 140 mm
- Weight 10 kg
- Temperature sensor on request
- Art.nr.81402 (230V)
- Incl. 4 x spinbar

Zustzliche Informationen

Number of positions	4 in one row
Max Quantity	4 x 5 ltr
Motor Rating input(W)	4 x 35W
Motor Rating output(W)	4 x 15 W
Speed display	analog
Speed range(rpm)	50 - 1250rpm
Stirring bar length max(mm)	60 mm
Heat output	4 x 300 W
Heating rate	7 K/min
Heating temperature range	room temp.- 350C
Heat control	digital

LABORTECHNIK FRÃ¶BEL GMBH
Bazienstr. 18f, D-88131 Lindau (0049)017676986491 | kontakt(at)labequip.de

Heat control accuracy	1 K
Speed control	stepless
Adjustable safety circuit min	'-
Adjustable safety circuit max	'-
Connection for ext. temperature sensor	on request
Control accuracy with sensor	1 K
Temperatureconstancyinmedium	1 K
Dimensions (W x D x H)	550 x 245 x 140 mm
Weight(kg)	10 kg
Permissible ambient temperature	5 - 40 C
Permissible relative humidity	80 %
Protection class according to DIN EN 60529	IP 42
RS232 interface	'-
Analog output	'-
Voltage	220 - 230 V
Frequency	50/60 Hz
Power input	1350 W